

PRODUCT DESCRIPTION

The DS1360 / DS1368 contains an eight inch diameter speaker. The premium sized 690 cubic inch enclosure includes a rigid foam acoustical insert to eliminate standing waves and metallic resonance. Dynasound's DS1360 / DS1368 soundmasking speaker is designed for quick and easy installation above suspended ceilings and includes a dust-proof perforated steel baffle. The DS1360 / DS1368 provides uniform dispersion and is well suited for soundmasking, paging and music signals.

FEATURES

- Made in the USA
- Easily installed in upward facing, side facing or downward facing applications
- Internal 70.7 volt transformer with rotary volume control - or may be specified for eight ohm operation (specify DS1368)
- Single point suspension for easy installation
- Material and construction permits use where ceiling plenum is part of the air handling system



TECHNICAL SPECIFICATIONS

Loudspeaker:	Eight inch diameter premium loudspeaker
DS1360 Transformer:	Primary 70.7v, Secondary 8 Ohms, Switch Positions: 1/4, 1/2, 1, 2, 4 watts
Dimensions:	11.5 inches x 11.5 inches x 6.25 inches tall
Weight:	8 lbs.
Finish:	White
Average sensitivity:	95 dB SPL 1 W 1 M
Loudspeaker power rating:	20 W
Magnet:	10 oz. ceramic

USE WITH:



DS1042 System



DS1092 System



DS1625 Amplifier



DS1628 Amplifier



DSRMP-Attenuator